

# Spindle ball bearing KH 61910 C TA P4+

16.07.2024



## Components

Bearing designation:	KH 61910 C TA
Bearing design:	KH
Series / size:	61910
Ball material:	Steel 100Cr6
Cage:	TA
Seal:	2RZ optional (with grease)
Precision:	P4+
Main dimensions [d x D x B]:	50 x 72 x 12 mm

## Load data

Static load capacity	$C_{0r}$ : 5600 N
Dynamic load capacity	$C_r$ : 7500 N
Fatigue load limit	$C_U$ : 290 N
Speed limit	$n_{grease}$ : 26250 1/min
Speed limit	$n_{oil}$ : 35000 1/min
Light preload	L: 40 N
Axial rigidity	$C_{ax}$ : 44 N/ $\mu$ m
Medium preload	M: 110 N
Axial rigidity	$C_{ax}$ : 64 N/ $\mu$ m
Heavy preload	S: 230 N
Axial rigidity	$C_{ax}$ : 86 N/ $\mu$ m
Spring preload	Ff: 360 N (for $n_{max}$ )

## Geometrical Data

Bore diameter	d: 50 mm	Oiling nozzle position	$d_7$ : 58.3 mm
Outer diameter	D: 72 mm	Pitch circle diameter	$d_m$ : 59.7 mm
Width of single bearing	B: 12 mm	Inner diameter of outer ring	$D_1$ : 63.1 mm
Ball diameter	$D_w$ : 4.762 mm	Undercut of associated component	$r_{a max}$ : 0.6 mm
Number of balls	Z: 30	Undercut of associated component (open side)	$r_{b max}$ : 0.3 mm
Chamfer (min)	$r_{1,2 min}$ : 0.6 mm	Abutment diameter inner ring	$d_{a,b min}$ : 53.3 mm
Chamfer (min), open side	$r_{3,4 min}$ : 0.3 mm	Abutment diameter outer ring	$D_{a,b max}$ : 69 mm
Outer diameter of inner ring	$d_1$ : 56.8 mm	Inner diameter of outer ring (open side)	$D_2$ : 64.6 mm
Outer diameter of inner ring (open side)	$d_2$ : 55.3 mm	Bearing weight	m: 0.14 kg
		Contact angle	Alpha 0: 17°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.