

# Spindle ball bearing HY S 61921 E TA P4+

16.07.2024



## Components

Bearing designation:	HY S 61921 E TA
Bearing design:	S
Series / size:	61921
Ball material:	Ceramic
Cage:	TA
Seal:	2RZ upon request
Precision:	P4+
Main dimensions [d x D x B]:	105 x 145 x 20 mm

## Load data

Static load capacity	$C_{0r}$ : 54500 N
Dynamic load capacity	$C_r$ : 49500 N
Fatigue load limit	$C_U$ : 1849 N
Speed limit	$n_{grease}$ : 10875 1/min
Speed limit	$n_{oil}$ : 14500 1/min
Light preload	L: 420 N
Axial rigidity	$C_{ax}$ : 273 N/ $\mu$ m
Medium preload	M: 1250 N
Axial rigidity	$C_{ax}$ : 409 N/ $\mu$ m
Heavy preload	S: 2510 N
Axial rigidity	$C_{ax}$ : 539 N/ $\mu$ m
Spring preload	Ff: 3510 N (for $n_{max}$ )

## Geometrical Data

Bore diameter	d: 105 mm	Oiling nozzle position	$d_f$ : 121.5 mm
Outer diameter	D: 145 mm	Pitch circle diameter	$d_m$ : 125 mm
Width of single bearing	B: 20 mm	Inner diameter of outer ring	$D_1$ : 132.2 mm
Ball diameter	$D_w$ : 11.906 mm	Undercut of associated component	$r_{a max}$ : 0.6 mm
Number of balls	Z: 26	Undercut of associated component (open side)	$r_{b max}$ : 0.6 mm
Chamfer (min)	$r_{1,2 min}$ : 0.6 mm	Abutment diameter inner ring	$d_{a,b min}$ : 110.7 mm
Chamfer (min), open side	$r_{3,4 min}$ : 0.6 mm	Abutment diameter outer ring	$D_{a,b max}$ : 140.2 mm
Outer diameter of inner ring	$d_1$ : 117.8 mm	Inner diameter of outer ring (open side)	$D_2$ : 137.1 mm
Outer diameter of inner ring (open side)	$d_2$ : -	Bearing weight	m: 0.71 kg
		Contact angle	Alpha 0: 25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.