

# Spindle ball bearing HY KH 6010 E TXM P4+

16.07.2024



## Components

Bearing designation:	HY KH 6010 E TXM
Bearing design:	KH
Series / size:	6010
Ball material:	Ceramic
Cage:	TXM
Seal:	2RZ optional (with grease)
Precision:	P4+
Main dimensions [d x D x B]:	50 x 80 x 16 mm

## Load data

Static load capacity	$C_{0r}$ : 7350 N
Dynamic load capacity	$C_r$ : 11100 N
Fatigue load limit	$C_U$ : 279 N
Speed limit	$n_{grease}$ : 27750 1/min
Speed limit	$n_{oil}$ : 37000 1/min
Light preload	L: 90 N
Axial rigidity	$C_{ax}$ : 111 N/ $\mu$ m
Medium preload	M: 280 N
Axial rigidity	$C_{ax}$ : 166 N/ $\mu$ m
Heavy preload	S: 560 N
Axial rigidity	$C_{ax}$ : 214 N/ $\mu$ m
Spring preload	Ff: 530 N (for $n_{max}$ )

## Geometrical Data

Bore diameter	d: 50 mm	Oiling nozzle position	$d_f$ : 61.9 mm
Outer diameter	D: 80 mm	Pitch circle diameter	$d_m$ : 63.8 mm
Width of single bearing	B: 16 mm	Inner diameter of outer ring	$D_1$ : 68 mm
Ball diameter	$D_w$ : 6.35 mm	Undercut of associated component	$r_{a max}$ : 1 mm
Number of balls	Z: 25	Undercut of associated component (open side)	$r_{b max}$ : 0.6 mm
Chamfer (min)	$r_{1,2 min}$ : 1 mm	Abutment diameter inner ring	$d_{a,b min}$ : 54.6 mm
Chamfer (min), open side	$r_{3,4 min}$ : 0.6 mm	Abutment diameter outer ring	$D_{a,b max}$ : 76 mm
Outer diameter of inner ring	$d_1$ : 59.7 mm	Inner diameter of outer ring (open side)	$D_2$ : 70.3 mm
Outer diameter of inner ring (open side)	$d_2$ : 58 mm	Bearing weight	m: 0.255 kg
		Contact angle	Alpha 0: 25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.