

# Spindle ball bearing HY S 6007 C TXM P4+

16.07.2024



## Components

Bearing designation:	HY S 6007 C TXM
Bearing design:	S
Series / size:	6007
Ball material:	Ceramic
Cage:	TXM
Precision:	P4+ (UP+ Upon request)
Main dimensions [d x D x B]:	35 x 62 x 14 mm

## Load data

Static load capacity	$C_{0r}$ : 15000 N
Dynamic load capacity	$C_r$ : 20600 N
Fatigue load limit	$C_U$ : 568 N
Speed limit	$n_{grease}$ : 33000 1/min
Speed limit	$n_{oil}$ : 44000 1/min
Light preload	L: 100 N
Axial rigidity	$C_{ax}$ : 53 N/ $\mu$ m
Medium preload	M: 300 N
Axial rigidity	$C_{ax}$ : 87 N/ $\mu$ m
Heavy preload	S: 600 N
Axial rigidity	$C_{ax}$ : 123 N/ $\mu$ m
Spring preload	Ff: 620 N (for $n_{max}$ )

## Geometrical Data

Bore diameter	d: 35 mm	Oiling nozzle position	$d_T$ : 46.1 mm
Outer diameter	D: 62 mm	Pitch circle diameter	$d_m$ : 48.5 mm
Width of single bearing	B: 14 mm	Inner diameter of outer ring	$D_1$ : 53.1 mm
Ball diameter	$D_w$ : 7.938 mm	Undercut of associated component	$r_{a max}$ : 1 mm
Number of balls	Z: 16	Undercut of associated component (open side)	$r_{b max}$ : 0.6 mm
Chamfer (min)	$r_{1,2 min}$ : 1 mm	Abutment diameter inner ring	$d_{a,b min}$ : 40.2 mm
Chamfer (min), open side	$r_{3,4 min}$ : 0.6 mm	Abutment diameter outer ring	$D_{a,b max}$ : 57.7 mm
Outer diameter of inner ring	$d_1$ : 43.2 mm	Inner diameter of outer ring (open side)	$D_2$ : 56.6 mm
Outer diameter of inner ring (open side)	$d_2$ : -	Bearing weight	m: 0.13 kg
		Contact angle	Alpha 0: 15°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.