

Spindle ball bearing HY S 61909 E TA P4+

16.07.2024



Components


| | |
|------------------------------|----------------------------|
| Bearing designation: | HY S 61909 E TA |
| Bearing design: | S |
| Series / size: | 61909 |
| Ball material: | Ceramic |
| Cage: | TA |
| Seal: | 2RZ optional (with grease) |
| Precision: | P4+ |
| Main dimensions [d x D x B]: | 45 x 68 x 12 mm |

Load data

| | |
|-----------------------|----------------------------|
| Static load capacity | C_{0r} : 12500 N |
| Dynamic load capacity | C_r : 14300 N |
| Fatigue load limit | C_U : 472 N |
| Speed limit | n_{grease} : 24000 1/min |
| Speed limit | n_{oil} : 32000 1/min |
| Light preload | L: 120 N |
| Axial rigidity | C_{ax} : 125 N/ μ m |
| Medium preload | M: 360 N |
| Axial rigidity | C_{ax} : 190 N/ μ m |
| Heavy preload | S: 720 N |
| Axial rigidity | C_{ax} : 252 N/ μ m |
| Spring preload | Ff: 900 N (for n_{max}) |

Geometrical Data

| | | | |
|--|------------------------|--|-------------------------|
| Bore diameter | d: 45 mm | Oiling nozzle position | d_f : 54.5 mm |
| Outer diameter | D: 68 mm | Pitch circle diameter | d_m : 56.5 mm |
| Width of single bearing | B: 12 mm | Inner diameter of outer ring | D_1 : 60.7 mm |
| Ball diameter | D_w : 6.35 mm | Undercut of associated component | $r_{a max}$: 0.6 mm |
| Number of balls | Z: 20 | Undercut of associated component (open side) | $r_{b max}$: 0.3 mm |
| Chamfer (min) | $r_{1,2 min}$: 0.6 mm | Abutment diameter inner ring | $d_{a,b min}$: 48.8 mm |
| Chamfer (min), open side | $r_{3,4 min}$: 0.3 mm | Abutment diameter outer ring | $D_{a,b max}$: 64.7 mm |
| Outer diameter of inner ring | d_1 : 52.3 mm | Inner diameter of outer ring (open side) | D_2 : 62.9 mm |
| Outer diameter of inner ring (open side) | d_2 : - | Bearing weight | m: 0.11 kg |
| | | Contact angle | Alpha 0: 25° |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.