

# Spindle ball bearing HY SM 608 C TA P4+

16.07.2024



## Components

Bearing designation:	HY SM 608 C TA
Bearing design:	SM
Series / size:	608
Ball material:	Ceramic
Cage:	TA
Precision:	P4+ (UP+ Upon request)
Main dimensions [d x D x B]:	8 x 22 x 7 mm

## Load data

Static load capacity	$C_{0r}$ : 950 N
Dynamic load capacity	$C_r$ : 2700 N
Fatigue load limit	$C_U$ : 36 N
Speed limit	$n_{grease}$ : 127500 1/min
Speed limit	$n_{oil}$ : 170000 1/min
Light preload	L: 13 N
Axial rigidity	$C_{ax}$ : 11 N/ $\mu$ m
Medium preload	M: 40 N
Axial rigidity	$C_{ax}$ : 17 N/ $\mu$ m
Heavy preload	S: 80 N
Axial rigidity	$C_{ax}$ : 24 N/ $\mu$ m
Spring preload	Ff: 40 N (for $n_{max}$ )

## Geometrical Data

Bore diameter	d: 8 mm	Oiling nozzle position	$d_T$ : 13.4 mm
Outer diameter	D: 22 mm	Pitch circle diameter	$d_m$ : 14.7 mm
Width of single bearing	B: 7 mm	Inner diameter of outer ring	$D_1$ : 17.6 mm
Ball diameter	$D_w$ : 3.969 mm	Undercut of associated component	$r_{a max}$ : 0.3 mm
Number of balls	Z: 9	Undercut of associated component (open side)	$r_{b max}$ : 0.3 mm
Chamfer (min)	$r_{1,2 min}$ : 0.3 mm	Abutment diameter inner ring	$d_{a,b min}$ : 10.2 mm
Chamfer (min), open side	$r_{3,4 min}$ : 0.3 mm	Abutment diameter outer ring	$D_{a,b max}$ : 20.5 mm
Outer diameter of inner ring	$d_1$ : 11.8 mm	Inner diameter of outer ring (open side)	$D_2$ : 18.7 mm
Outer diameter of inner ring (open side)	$d_2$ : -	Bearing weight	m: 0.01 kg
		Contact angle	Alpha 0: 15°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.