

Labyrinth Metal Seal Type M



M 200 X 230 X 20

Item number 301470

Technical data

| | |
|------------------------------|--|
| Outer ring material*: | Aluminum (GD AISi 12) |
| Inner ring material: | Unalloyed construction steel |
| Inner diameter ID: | 200 mm |
| Outer diameter OD: | 230 mm |
| Installed width W: | 20 mm |
| Sealing gap: | Horizontal |
| Axial play S_{ax}^{**} : | 0.8 mm |
| Radial play S_{rad}^{**} : | $S_{rad} = S_{ax} / \tan(42,5^\circ)$ |
| Gap diameter e: | 224.5 mm |
| Gap height: | Constant 0,2– 0,5 mm (depending upon size) |
| Keyway width c: | 5 mm |
| Speed limit: | 4500 rpm |
| Weight: | 1.1773 kg |
| Operating temperature t: | -40° - 200°C |

*Aluminum outer ring
The aluminum outer ring can be slightly non-round as supplied. By pressing in the seal, the relatively easily deformable ring fits the roundness of the hub.
The outer ring can be up to 0.1 mm wider than the inner ring due to manufacturing. GMN metal labyrinth seals are pressed through a calibration ring ('zero dimension'). The outer ring then springs back due to its elasticity.

**Entire movability from one end position to the other.

Heavy and direct splashing liquids could be drained through a certain number of grooves in the outer ring into a circular groove inside the housing; Width of the circular groove in the customer part: $R = c + 1$ mm ($c =$ Keyway width)

Installation

"l" Length (chamfering of shaft and housing) depending on the width W: $l = 0,1 \times B$

Component tolerances

Surrounding structure (mating parts)

Housing: K7 / Shaft: h6
Surface quality: $R_z \leq 16 \mu\text{m}$; $R_a \leq 3,2 \mu\text{m}$

Axial play:

