

# Spindle ball bearing HY KH 6012 E TA P4+

16.07.2024



## Components

|                              |                            |
|------------------------------|----------------------------|
| Bearing designation:         | HY KH 6012 E TA            |
| Bearing design:              | KH                         |
| Series / size:               | 6012                       |
| Ball material:               | Ceramic                    |
| Cage:                        | TA                         |
| Seal:                        | 2RZ optional (with grease) |
| Precision:                   | P4+                        |
| Main dimensions [d x D x B]: | 60 x 95 x 18 mm            |

## Load data

|                       |                            |
|-----------------------|----------------------------|
| Static load capacity  | $C_{0r}$ : 11000 N         |
| Dynamic load capacity | $C_r$ : 16200 N            |
| Fatigue load limit    | $C_U$ : 416 N              |
| Speed limit           | $n_{grease}$ : 23250 1/min |
| Speed limit           | $n_{oil}$ : 31000 1/min    |
| Light preload         | L: 140 N                   |
| Axial rigidity        | $C_{ax}$ : 135 N/ $\mu$ m  |
| Medium preload        | M: 400 N                   |
| Axial rigidity        | $C_{ax}$ : 196 N/ $\mu$ m  |
| Heavy preload         | S: 800 N                   |
| Axial rigidity        | $C_{ax}$ : 252 N/ $\mu$ m  |
| Spring preload        | Ff: 790 N (for $n_{max}$ ) |

## Geometrical Data

|  |                        |  |                         |
|--|------------------------|--|-------------------------|
| Bore diameter                            | d: 60 mm               | Oiling nozzle position                       | $d_f$ : 74.4 mm         |
| Outer diameter                           | D: 95 mm               | Pitch circle diameter                        | $d_m$ : 76.5 mm         |
| Width of single bearing                  | B: 18 mm               | Inner diameter of outer ring                 | $D_1$ : 81.5 mm         |
| Ball diameter                            | $D_w$ : 7.938 mm       | Undercut of associated component             | $r_{a max}$ : 1 mm      |
| Number of balls                          | Z: 24                  | Undercut of associated component (open side) | $r_{b max}$ : 1 mm      |
| Chamfer (min)                            | $r_{1,2 min}$ : 1.1 mm | Abutment diameter inner ring                 | $d_{a,b min}$ : 65.7 mm |
| Chamfer (min), open side                 | $r_{3,4 min}$ : 1 mm   | Abutment diameter outer ring                 | $D_{a,b max}$ : 90.1 mm |
| Outer diameter of inner ring             | $d_1$ : 71.9 mm        | Inner diameter of outer ring (open side)     | $D_2$ : 84.6 mm         |
| Outer diameter of inner ring (open side) | $d_2$ : 70.7 mm        | Bearing weight                               | m: 0.4 kg               |
|  |                        | Contact angle                                | Alpha 0: 25°            |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.