

Spindle ball bearing S 619/5 C TA P4+

16.07.2024



Components


Bearing designation:	S 619/5 C TA
Bearing design:	S
Series / size:	619/5
Ball material:	Steel 100Cr6
Cage:	TA
Precision:	P4+
Main dimensions [d x D x B]:	5 x 13 x 4 mm

Load data

Static load capacity	C_{0r} : 430 N
Dynamic load capacity	C_r : 1200 N
Fatigue load limit	C_U : 22 N
Speed limit	n_{grease} : 142500 1/min
Speed limit	n_{oil} : 190000 1/min
Light preload	L: 6 N
Axial rigidity	C_{ax} : 7 N/ μ m
Medium preload	M: 18 N
Axial rigidity	C_{ax} : 11 N/ μ m
Heavy preload	S: 36 N
Axial rigidity	C_{ax} : 15 N/ μ m
Spring preload	Ff: 25 N (for n_{max})

Geometrical Data

Bore diameter	d: 5 mm	Oiling nozzle position	d_T : 8.1 mm
Outer diameter	D: 13 mm	Pitch circle diameter	d_m : 8.9 mm
Width of single bearing	B: 4 mm	Inner diameter of outer ring	D_1 : 10.7 mm
Ball diameter	D_w : 2.381 mm	Undercut of associated component	$r_{a \max}$: 0.2 mm
Number of balls	Z: 8	Undercut of associated component (open side)	$r_{b \max}$: 0.2 mm
Chamfer (min)	$r_{1,2 \min}$: 0.2 mm	Abutment diameter inner ring	$d_{a,b \min}$: 6.3 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.2 mm	Abutment diameter outer ring	$D_{a,b \max}$: 12 mm
Outer diameter of inner ring	d_1 : 7.1 mm	Inner diameter of outer ring (open side)	D_2 : 11.3 mm
Outer diameter of inner ring (open side)	d_2 : -	Bearing weight	m: 0.002 kg
		Contact angle	Alpha 0: 15°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.