

Spindle ball bearing HY S 6001 C TA P4+

16.07.2024



Components

| | |
|------------------------------|------------------------|
| Bearing designation: | HY S 6001 C TA |
| Bearing design: | S |
| Series / size: | 6001 |
| Ball material: | Ceramic |
| Cage: | TA |
| Precision: | P4+ (UP+ Upon request) |
| Main dimensions [d x D x B]: | 12 x 28 x 8 mm |

Load data

| | |
|-----------------------|----------------------------|
| Static load capacity | C_{0r} : 2900 N |
| Dynamic load capacity | C_r : 5900 N |
| Fatigue load limit | C_U : 109 N |
| Speed limit | n_{grease} : 78750 1/min |
| Speed limit | n_{oil} : 105000 1/min |
| Light preload | L: 30 N |
| Axial rigidity | C_{ax} : 22 N/ μ m |
| Medium preload | M: 90 N |
| Axial rigidity | C_{ax} : 36 N/ μ m |
| Heavy preload | S: 180 N |
| Axial rigidity | C_{ax} : 51 N/ μ m |
| Spring preload | Ff: 120 N (for n_{max}) |

Geometrical Data

| | | | |
|--|------------------------|--|-------------------------|
| Bore diameter | d: 12 mm | Oiling nozzle position | d_T : 18.5 mm |
| Outer diameter | D: 28 mm | Pitch circle diameter | d_m : 20 mm |
| Width of single bearing | B: 8 mm | Inner diameter of outer ring | D_1 : 23.4 mm |
| Ball diameter | D_w : 4.762 mm | Undercut of associated component | $r_{a max}$: 0.3 mm |
| Number of balls | Z: 11 | Undercut of associated component (open side) | $r_{b max}$: 0.3 mm |
| Chamfer (min) | $r_{1,2 min}$: 0.3 mm | Abutment diameter inner ring | $d_{a,b min}$: 14.6 mm |
| Chamfer (min), open side | $r_{3,4 min}$: 0.3 mm | Abutment diameter outer ring | $D_{a,b max}$: 26.2 mm |
| Outer diameter of inner ring | d_1 : 16.7 mm | Inner diameter of outer ring (open side) | D_2 : 24.8 mm |
| Outer diameter of inner ring (open side) | d_2 : - | Bearing weight | m: 0.017 kg |
| | | Contact angle | Alpha 0: 15° |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.