

# Spindle ball bearing HY S 61804 C TA P4+

16.07.2024



## Components

Bearing designation:	HY S 61804 C TA
Bearing design:	S
Series / size:	61804
Ball material:	Ceramic
Cage:	TA
Precision:	P4+
Main dimensions [d x D x B]:	20 x 32 x 7 mm

## Load data

Static load capacity	$C_{0r}$ : 2420 N
Dynamic load capacity	$C_r$ : 3650 N
Fatigue load limit	$C_U$ : 92 N
Speed limit	$n_{grease}$ : 61500 1/min
Speed limit	$n_{oil}$ : 82000 1/min
Light preload	L: 19 N
Axial rigidity	$C_{ax}$ : 22 N/ $\mu$ m
Medium preload	M: 55 N
Axial rigidity	$C_{ax}$ : 35 N/ $\mu$ m
Heavy preload	S: 110 N
Axial rigidity	$C_{ax}$ : 49 N/ $\mu$ m
Spring preload	Ff: 100 N (for $n_{max}$ )

## Geometrical Data

Bore diameter	d: 20 mm	Oiling nozzle position	$d_T$ : 24.9 mm
Outer diameter	D: 32 mm	Pitch circle diameter	$d_m$ : 26 mm
Width of single bearing	B: 7 mm	Inner diameter of outer ring	$D_1$ : 28.1 mm
Ball diameter	$D_w$ : 3.175 mm	Undercut of associated component	$r_{a max}$ : 0.3 mm
Number of balls	Z: 18	Undercut of associated component (open side)	$r_{b max}$ : 0.3 mm
Chamfer (min)	$r_{1,2 min}$ : 0.3 mm	Abutment diameter inner ring	$d_{a,b min}$ : 21.8 mm
Chamfer (min), open side	$r_{3,4 min}$ : 0.3 mm	Abutment diameter outer ring	$D_{a,b max}$ : 30.5 mm
Outer diameter of inner ring	$d_1$ : 23.9 mm	Inner diameter of outer ring (open side)	$D_2$ : 29.2 mm
Outer diameter of inner ring (open side)	$d_2$ : -	Bearing weight	m: 0.016 kg
		Contact angle	Alpha 0: 15°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.